



CW³ 60000 SH Automatic Checkweigher

www.loma.com

Versatile, proven Super-HeavyWeight checkweighing systems for the food and packaging industries



- **Versatile** Bag or case weighing up to 60kgs
- **Accurate** Excellent accuracy, especially with flexible packaging
- **Fast** Belt speeds up to 54 m/min
- **Reliable** Heavy duty conveyor components, high quality electronics
- **Accredited** OIML R51 and EC TAC (MID) approved
- **Easy to use** Full colour graphical touch screen
- **Environment** Wide operating temperature range 0-40 °C



Metal Detection

X-ray Inspection

Checkweighers

Data Capture

Designed to Survive




CW³ 60000 SH Automatic Checkweigher

Finish:	304 stainless steel with brushed finish
Available Line Heights:	750 mm - 1100mm
Available PWT Lengths:	800mm - 1000mm
Minimum / Maximum Weight:	1kg—60kg
Maximum Product Width:	500mm
Maximum Product Length:	900mm (platform dependent)
Typical Accuracy, Un:	1.8g
Maximum Speed:	54 m/min
Capacity	Up to 120ppm
Supply Voltages:	110 or 230V/1ph/N+E 50 or 60Hz
Air Supply:	5 to 8 bar
Typical Reject Options:	Pusher, Diverter
Environment:	IP65
Belt type:	Food quality flat belt - quick release (no tools required)
Standard inclusions:	Adjustable feet, USB socket, Multi speed, Pack pitch monitor, LED Indicator Stack
Options:	Servo feedback signal - for filler control, Serial Link, LomaEnet, Makrolon covers, 316 stainless steel, reject bin



Technical Specification

- Stainless steel construction
- Product specific filtering
- Automatic mean weight correction
- Sample packs function
- Multi-product memory (500)
- Brushless motors
- High capacity loadcell
- True multi-speed
- R51/MID approved



QPM Ltd., Unit 12, Robinhood Business Park, Robinhood Road, Dublin 22, Ireland
Tel: +353 (0) 1 450 2421, Fax: +353 (0) 1 450 2311,
Email: mnevin@qpm.ie Web: www.qpm.ie



Designed to Survive