


Bolphane® BX

Multipurpose Shrink Film

- High degree of shrink force, ideal for multipacking applications.
- Excellent stiffness and flatness particularly adapted for singlewound applications.
- Broad sealing characteristics, including static sealing.
- Superior optics

APPLICATIONS

➔ Due to its very good mechanical properties, Bolphane BX is a versatile film, which is able to run on a variety of machines and equipment for all types of applications.



➔ Its stiffness and lay flat, combined with good tensile strength make BX the ideal product for multipacking application. Excellent gloss and clarity add to its presence.

Bolloré Inc.
60 Louisa Viens Dr
Dayville, CT 06241
Sales: 800-343-0358
www.bolloréinc.com




Rev.6/01/2012

Bolloré

Bolphane® BX

TENSILE STRENGTH

- Versatile, BX offers higher tensile strength and stiffness at equivalent thickness.



TECHNICAL FEATURES

PROPERTIES	50 GAUGE	60 GAUGE	75 GAUGE	100 GAUGE
Yield (MSI per pound)	59,3	51,4	40,6	30,9
Gloss (85°) (%)	118			
Haze (%)	2,5			3
Free Shrink (%) at 200°F	20			
at 250°F	50			
Seal strength (g/inch)	1600	2 000	2 100	2 300
WVTR (gms/100 sq.in/24 hrs at 95% HR, 95°F)	1,0	0,9	0,7	0,5
O ₂ Permeability (cc/m ² /24 hrs at 73°F, 1 atm)	8500	7 000	5 500	4 000
Length of the roll (Ft) Singlewound BX-SW	10500	8 750	7 000	5 250
Centerfolded BX-CF	5250	4 375	3 500	2 625
Core Internal Diameter (inch)	3"			
Nominal roll outside diameter (inch)	9" 1/2			

STANDARD PUT-UPS

- Bolphane BX is available in Singlewound (BX-SW) or in Centerfolded (BX-CF). For any other requirement, please contact us.

TYPE	WIDTH (inch)		
	mini	maxi	increment
BX-SW		78"	1/4"
BX-CF		40"	1"

Bolloré